



- 1 BRASS PER ASTM-B-16
- 2 PTFE
- 3 PHOSPHOR BRONZE PER ASTM-B-139
- 4 NICKEL PLATE PER QQ-N-290
- 5 GOLD PLATE PER ASTM-B-488
- 6 TIN-LEAD PER ASTM B571 (PB 3% TO 13% BY WEIGHT)
- 7 CUSTOMER METHOD FOR MOUNTING CONNECTOR MUST PREVENT ANY MOVEMENT OF CONNECTOR DURING MATING, IN SERVICE, OR UNMATING.
- 8 TIN PER ASTM B545

PCB CONFIGURATION  
NTS

8	2016080-2
6	2016080-1
ACTION PIN	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DW	D. WALLACE	30APR2008
DIMENSIONS: INCHES		CHK	F. BLASICK	30APR2008
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	F. BLASICK	30APR2008
0 PLC	± .005	NAME		
1 PLC	± .005	PRODUCT SPEC		
2 PLC	± .005	108-2340		
3 PLC	± .005	APPLICATION SPEC		
4 PLC	± .005	SIZE		
ANGLES	± .005	CAGE CODE		
MATERIAL	FINISH	DRAWING NO		RESTRICTED TO
		A100779C=2016080		
CUSTOMER DRAWING		SCALE 10:1		SHEET 1 OF 1 REV C